

Technical Data Sheet

For domestic range hoods according to (EU) No 65/2014 and (EU) No 66/2014:

| | |
|--|-------------------------|
| Supplier's name or trade mark | CAPLE |
| Type/Description | CGC711BK |
| Energy efficiency class ❶ | C |
| Annual energy consumption | 52kWh/a |
| Fluid Dynamic Efficiency class ❷ | D |
| Lighting efficiency class | A |
| Grease Filtering Efficiency class | C |
| Maximum air flow | 456 m ³ /h |
| Measured air flow rate at best efficiency point | 230.3 m ³ /h |
| Measured air pressure at best efficiency point | 241 Pa |
| Measured electric power input at best efficiency point | 94.5W |
| Average illumination of the lighting system on the cooking surface | 157lux |
| Measured power consumption in standby mode | / |
| Measured power consumption off mode | 0.49W |
| Sound power level | 56dB |
| Mounting | Wall mounting |
| Size | 700mm |
| Rated Power | 104W |
| Rated volatge/frequency | 220-240V 50/60Hz |

Note:

❶ A(highest efficiency) to F (lowest efficiency)

❷ A(highest efficiency) to F (lowest efficiency)

The above values have been measured in accordance with standards under specified operating conditions.

The above is based on the European Union's standards and rules.